

AMENDMENTS TO THE SPECIFICATION

Please amend paragraph number 00014 (which is on page 3 of the specification) to read as follows:

Projecting inwardly from the internal diameter of the floating seal are surfaces 22 and 23 which are dimensioned to engage and seal with the cylindrical outer surface of a male coupling member (not shown). The floating seal 20 may be an elastomeric material such as [[PEEK]] polyetherketone (PEEK), or other materials that are sufficiently resilient and compressible to form a fluid tight seal with the male coupling member. Preferably, the inner diameter of surfaces 22 and 23 may be slightly less than the outer diameter of the male coupling member.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY. **IMAGES ARE**
As rescanning these documents will not correct the image.
problems checked, please do not report these problems to
the IFW Image Problem Mailbox. **the IFW Image**